



### NOTES

1. HOT DIP GALVANIZE PER ASTM SPEC. A153 (LATEST REVISION)
2. STAMP ROD BEFORE GALV. AS SHOWN IN TABLE WITH 1/4" FLAT CHARACTERS. MUST BE READABLE AFTER GALV.
3. ADD USA SUFFIX TO CATALOG NUMBER FOR BUY AMERICA ITEMS. PURCHASERS OF BUY AMERICA ITEMS WILL BE PROVIDED A DATED CERTIFICATE OF COMPLIANCE TO SPECIFIC BUY AMERICA PROVISIONS IF REQUESTED AT THE TIME OF ORDER. CONTACT HUBBELL POWER SYSTEMS CUSTOMER SERVICE FOR DETAILS.

| CAT. NO.  | DESCRIPTION            | "A"   | STENCIL |
|-----------|------------------------|-------|---------|
| 5315      | THREADED THIMBLEYE ROD | 60.00 | C-5/8-5 |
| 5316      | THREADED THIMBLEYE ROD | 72.00 | C-5/8-6 |
| 5317      | THREADED THIMBLEYE ROD | 84.00 | C-5/8-7 |
| 5318      | THREADED THIMBLEYE ROD | 96.00 | C-5/8-8 |
| E100-0106 | THREADED THIMBLEYE ROD | 84.00 | C-5/8-7 |
| T5316G    | THREADED THIMBLEYE ROD | 72.00 | G-5/8-6 |
| T5317G    | THREADED THIMBLEYE ROD | 84.00 | G-5/8-7 |
| T5318G    | THREADED THIMBLEYE ROD | 96.00 | G-5/8-8 |

|   |                   |   |                |
|---|-------------------|---|----------------|
| CHANCE<br>TOLERANCE CHART   |                   | HUBBELL POWER SYSTEMS                     |                |
| CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED. ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS. |                   | TITLE<br>THREADED<br>THIMBLEYE ROD - 5/8" |                |
| SIZE<br>C   | DWG NO.<br>SA5315 | QTY / PART / ASSY NO.<br>SEE CHART        | REV<br>A       |
| DO NOT SCALE THIS DRAWING   | DRN BY MRG        | DATE 12/20/18                             | SHEET 01 OF 01 |