


CATALOG NUMBER	BELL CORE NUMBER	"A"
C2050140	-	6"
C2050141	-	8"
PSC2050606	400013843	10"
8882	400013850	12"
8884	400013868	14"
8886	400013876	16"
88862N	-	16"
8888	400013884	18"
88882N	-	18"
8890	400013892	20"
8892	-	22"
8894	-	24"
8896	-	26"
888962N	-	26"
8897	-	28"
8898	-	30"
889832	-	32"
PS889834	-	34"
PS889836	-	36"
PS889838	-	38"
PS889840	-	40"
PS889842	-	42"
PSDA345000	-	50"
PSDA347200	-	72"

-=NOTE=-

1. MATERIAL: STEEL, HOT DIP GALVANIZED PER ASTM A153.
2. RATED TENSILE STRENGTH 18,350 LBS. PER ANSI C135.1

<b>CHANCE</b> ®		 <b>HUBBELL POWER SYSTEMS, INC.</b>	
		TITLE <b>DOUBLE-ARMING BOLT</b>	
CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION, OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.	SIZE <b>B</b>	CAT / PART / ASSY NO. <b>SEE TABLE</b>	DO NOT SCALE THIS DRAWING
		DWG NO. <b>SA8882</b>	REV <b>E</b>
		DATE 9/27/19	SHEET 1 OF 1